




# Living Shorelines - Evolving Design Considerations for Sustainable Projects

Doug Baughman  
*Senior Principal Technologist*



# Living shorelines are no longer new!

- Many projects have now been installed across the US
- Most have been small to medium sized projects
- Larger and more expensive projects are emerging
- ***More emphasis on measuring success and demonstrating ecological and economic value***



# Living Shorelines design considerations...there are many!

- Existing erosion rate
- Existing shore morphology
- Depth offshore
- Nearshore morphology & substrate stability
- Wave climate
- Presence of submerged aquatic vegetation (SAV)
- Tide range
- Storm surge
- Vegetation
- Sediment transport

*The same coastal processes that apply to design of traditional engineering solutions apply to living shorelines...*



<http://ccrm.vims.edu/livingshorelines/>




Understanding coastal processes is key to project success!



# Eastern Neck National Wildlife Refuge has a history of erosion issues


- “The USFWS highest priority over the next 15 years is to protect against additional refuge shoreline erosion and loss of refuge tidal marsh....”






# In-depth coastal studies completed to support project design


- Data collection and analysis
- Wind extremes determination → MIKE EVA
- Wave modelling → MIKE 21 SW FM
- Current modelling → MIKE 21 HD FM
- Beach stability modelling → Storm Induced BEAch Change model (SBEACH by USACE)
- Conceptual design based on 25yr return period storm



## 25yr Extreme Waves from N Direction



# Coastal process evaluation identified priority areas for restoration




# Geotechnical survey conducted at key locations

- Sediment cores collected in January
- Used hand augers with casing to collect samples
- Subsurface soil density was determined using Dynamic Cone Penetrometer (DSP) tests
- Results used to determine potential for substrate to support construction materials






# Conceptual Design – Headland Breakwater Tombohos



These alignments are considered headland control since they are placed sufficiently close to existing hard points extending seaward from the shoreline. The purpose of these structures is to protect these shoreline headlands which help shape the bay shoreline by wave diffraction.

# Evaluating project benefits is becoming more critical

## Howard Beach, Queens Natural Infrastructure for Coastal Resilience Project



- CH2MHILL supported TNC on a case study examining a range of natural infrastructure solutions to reduce climate risks in the Howard Beach Neighborhood
- ***Goal was to compare the financial costs and benefits of a range of Natural-Grey engineering solutions under alternative climate change scenarios***
- Project was completed to provide input into the City of New York's Post Hurricane Sandy planning process


# Approach integrated modeling platforms to document flood risk reduction and ecological benefits









# Additional Grey Structures Needed for Full Protection (Alternative 4)



# Cost-Benefit Methodology Facilitated Integration of Economic Impact

4

## Cost Benefit Analysis



- Cost estimates
- Cost benefits
- Avoided cost
- Economic analysis

## Benefits

- Avoided damages compared to base case damages using Hazus —results in net “damage avoided”
- Ecosystem Service benefits from benefit-transfer of secondary literature

## Costs

- Estimates based on CH2M HILL cost estimating database
- ± 30% precision
- Natural Infrastructure O&M costs from NYC Parks and Recreation

B

C

Benefit/Cost ratio is a key output of benefit cost analysis

<http://www.nature.org/ourinitiatives/regions/northamerica/unitedstates/newyork/climate-energy/natural-infrastructure-study-at-howard-beach.xml>



# Living shoreline design considerations vary by location, scale, and project objectives

- Success of larger projects dependent on:
  - Adequate analysis of coastal processes
  - Sufficient geotechnical data
- Demonstration of project benefits:
  - Needs to include flood risk, wave attenuation, and ecological measures



Thank You

